

# MILL GRINGDER SERIES



## FEATURES

- Diamond grinding wheel.
- Low maintenance, good as a result of grinding.
- The engine is the frequency of electronic and strong, constant, outside the motor life.



## APPLICATIONS

Suitable for sharpening 2, 3, and 4-blade end mills:

- 2-Flute (2F) Collet Positioning Rings  
 $\varnothing 4 - \varnothing 5 - \varnothing 6 - \varnothing 8 - \varnothing 10 - \varnothing 12 - \varnothing 14 - \varnothing 16 - \varnothing 18 - \varnothing 20$
- 3-Flute (3F) Collet Positioning Rings  
 $\varnothing 4 - \varnothing 5 - \varnothing 6 - \varnothing 8 - \varnothing 10 - \varnothing 12 - \varnothing 14 - \varnothing 16 - \varnothing 18 - \varnothing 20$
- 4-Flute (4F) Collet Positioning Rings  
 $\varnothing 4 - \varnothing 5 - \varnothing 6 - \varnothing 8 - \varnothing 10 - \varnothing 12 - \varnothing 14 - \varnothing 16 - \varnothing 18 - \varnothing 20$

High-precision workpiece clamping system ensures accurate and stable sharpening.

Powerful motor provides smooth operation and consistent results.

Sharpening range from  $\varnothing 2$  to  $\varnothing 20$  mm with adjustable sharpening angle.

Compact design, easy to use, ideal for tool rooms and workshops.

## SPECIFICATION

MODEL	700-10-20	700-10-12
Input Voltage	220V / 50Hz	220V / 50Hz
Rated Power	600 W	600 W
Motor Speed	6000 rpm	6000 rpm
Grinding Range	$\varnothing 4 - \varnothing 20$ mm	$\varnothing 2 - \varnothing 12$ mm
Milling Cutter Type	2F / 3F / 4F	2F / 3F / 4F
Grinding Angle	Blade Angle: 5° / Rake Angle: 20° / Rake Angle: 25°	Blade Angle: 5° / Rake Angle: 20° / Rake Angle: 25°
Package Size	370 x 330 x 300 mm	365 x 330 x 265 mm
Net Weight	Approx. 18.5 kg	Approx. 12.1 kg

## STANDBY DELIVERY

NAME	QUANTITY
Main unit	1 pcs
Collet	10 pcs
2 flutes holder	5 pcs
3 flutes holder	5 pcs
4 flutes holder	5 pcs
Case	1 pcs
Hexagon wrench	1 pcs
Brush	1 pcs
Power cord	1 pcs

